

EXPRESS™ L6



ELECTRIC



GAS

BIGGER IS ALWAYS BETTER.

Outdo yourself by exploring more than ever before with the Express L6 series. With room for 6, rugged tires, and higher ground clearance, you'll elevate everyone's expectations for a smooth, stylish ride. Boost your drive time with the unbeatable power of our exclusive 72-volt powertrain or choose the industry's first closed-loop EFI powertrain. Here to awaken your sense of adventure, it's time to start crossing things off your bucket list with the Express L6.

KEY FEATURES

- 23-in Desert Eagle Tires
- Front Brush Guard
- Fold-Down Cargo Deck
- Headlights, Taillights and Brake Lights
- Dual USB Ports
- Horn
- Cupholders
- Dashboard Storage Pockets
- Premium Steering Wheel
- State of Charge Meter (Electric Only)
- DC/DC Converter (Electric Only)
- 72-Volt AC Powertrain (Electric Only)
- Rabbit/Turtle Speed Switch (Electric Only)
- Fuel Gauge (Gas Only)
- Low Oil Indicator (Gas Only)

DIMENSIONS

OVERALL LENGTH	143.5 in (364 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT (W/O ROOF)	53.5 in. (136 cm)
OVERALL HEIGHT (W/ ROOF)	72 in (183 cm)
WHEEL BASE	93.5 in (237 cm)
FRONT WHEEL TRACK	37.5 in (95 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE @ DIFFERENTIAL	7.0 in (18 cm)

POWER

POWER SOURCE	72 Volts AC	4 Cycle 24.5 cu in (401 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
MOTOR TYPE	AC Induction	N/A
FUEL SYSTEM	N/A	Closed-Loop Electronic Fuel Injection
HORSEPOWER (KW)	22.4 hp (16.7 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
ELECTRICAL SYSTEM	72 Volt	Starter/Generator - Solid State Regulator
BATTERIES (QTY/TYPE)	Six, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank
BATTERY CHARGER	72 VDC Delta Φ , 120/230 VAC, UL & CSA	N/A
SPEED CONTROLLER	350 Amp AC	N/A
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	
REAR AXLE RATIO	17:1	11.47:1 (Forward); 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	6-Passenger	
DRY WEIGHT	964 lbs. (437 kg)	870 lb (395 kg)
CURB WEIGHT	1560 lbs. (708 kg)	910 lb (413 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)	
SPEED (LEVEL GROUND)	16.5 mph \pm 0.5 mph (26 kph \pm 0.8 kph)	
LOW SPEED (LEVEL GROUND)	12 mph \pm 0.5 mph (19.3 kph \pm 0.8 kph)	N/A

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single Point Engagement
TIRES	Desert Eagle 23 x 10 - 14 on Alloy Wheel

BODY & CHASSIS

FRAME	Welded Steel with Powder-Coat Protection
BODY & FINISH	Injection Molded TPO
AVAILABLE BODY COLORS	Almond, Black, Electric Blue, Flame Red, Inferno Red, Metallic Charcoal, Ocean Grey, Platinum, White
AVAILABLE SEAT COLORS	Gray, Oyster, Tan, Black



LIVE LARGER



www.ezgo.com

Features and specifications of vehicles subject to change without notice. Vehicles as photographed may include options not included on base model. ©2019 Textron Specialized Vehicles Inc. 82455-G12 (Rev. 08/2019)

